



- ① Series No.
- ② No. of Circuits
- ③ Plating Code:
 - 1= 3.05 μm (120 μ "") Min. Tin
over 0.76 μm (30 μ "") Nickel
 - 2= Gold flash plated
over 1.27 μm (50 μ "") Nickel
 - 3= 0.38 μm (15 μ "") Gold plated over
1.27 μm (50 μ "") Nickel
 - 4= 0.76 μm (30 μ "") Gold plated over
1.27 μm (50 μ "") Nickel
- ④ V= Straight
- ⑤ Insulation: 1= PBT UL 94V-0, Color Black
A= Nylon 6T UL 94V-0, Color Black
- ⑥ Pin Length Option cord:
See Table PDF. File No. CH7101T

A = 2.00 * No. of Spaces
B = A + 2.0
* Available in 4 through 80 circuits

Recommended P.C. Board Layout

RoHS Compliant

4				CIVILUX.CORP 2006.01.31 ISSUED			DATE	UNIT: mm / inch		TITLE: 2.00MM(.079") STRAIGHT DUAL ROW BORAD MOUNT PIN HEADER		 瀚荃股份有限公司 CviLux Corporation			
3	Sun	1/19/06'	ECN06019		DRAWN BY:	Sun	1/24 06'	TOLERANCE UNLESS OTHERWISE SPECIFIED							
2	Casey	5/28/04'	ECN04208		ENGINEER:	Eisley	1/26 06'			.X±0.30/.012	X:±1"		MATERIAL:		
1	SUN	4/09/04'	ECN04144		CHECKED BY:	David	1/27 06'	.XX±0.20/.008	.X±					FINISH:	
SYM	NAME	DATE	REVISIONS		APPROVED BY:	Alex	1/27 06'			.XXX±0.10/ .004	.XX±				
												DRAWING NO.	CH7101SG	PART NO.	CH71***V***
												SCALE	4 / 1	SHEET	1 OF 1